

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
19 August 2004 (19.08.2004)

PCT

(10) International Publication Number  
**WO 2004/070906 A2**

- (51) International Patent Classification<sup>7</sup>: **H02H**
- (21) International Application Number:  
PCT/US2004/002727
- (22) International Filing Date: 30 January 2004 (30.01.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/444,573 3 February 2003 (03.02.2003) US  
10/757,743 15 January 2004 (15.01.2004) US
- (71) Applicant: LEVITON MANUFACTURING CO., INC.  
[US/US]; 59-25 Little Neck Parkway, Little Neck, NY  
11362 (US).
- (72) Inventors: GERMAIN, Frantz; 142-10 243 Street,  
Rosedale, NY 11422 (US). STEWART, Stephen; 4710-2  
Hillcrest Drive, Berrien Springs, MI 49103 (US).
- (74) Agents: SUTTON, Paul, J. et al.; Greenberg Traurig, LLP,  
885 Third Avenue, New York, NY 10022 (US).
- (81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


- (84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

**Published:**

- *without international search report and to be republished  
upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

(54) Title: GFCI RECEPTACLE HAVING BLOCKING MEANS



(57) Abstract: Located within a GFCI device having receptacle openings in its face is a movable contact bearing arm held in either a closed or open position by a latching member connected to a spring loaded reset button. The reset button assumes a first depressed position when the GFCI is in a conducting state, and a second extended position when the GFCI is in a non conducting state. A blocking member located within the body of the GFCI is adapted to be moved to a first position to blocks at least one opening of each receptacle, or to a second position to allow the prongs of a plug to enter the receptacle openings. When the GFCI is in the conducting state, the reset button is in its first position and holds the blocking member in its first position to permit the prongs of a plug to be inserted into the receptacle openings. When the GFCI is in a non-conducting state or is defective, the reset button and the blocking member are in their second positions and the prongs of a plug are prevented from entering the receptacle.